



# Safety Data Sheet

**STP Products Manufacturing Company**

44 Old Ridgebury Road  
 Suite 300  
 Danbury, CT 06810  
 Tel. 1-203-205-2900

## 1. Product And Company Identification

**Product Name:** STP® Diesel Fuel Treatment & Injector Cleaner

**Responsible Party:** STP Products Manufacturing Company  
 44 Old Ridgebury Road  
 Suite 300  
 Danbury, CT 06810

**Information Phone Number:** +1 203-205-2900

**Emergency Phone Number:**  
 For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)  
 For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for  
 Outside US and Canada (call collect)

**SDS Date of Preparation:** 01/31/2018

**Product Use and Uses Advised Against:** Automotive maintenance product – For consumer and professional use

## 2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

**GHS Classification:**

Physical:	Health:
Flammable Liquid Category 4	Skin Irritation Category 2 Carcinogen Category 2 Reproductive Toxicity Category 2 Specific Target Organ Toxicity Category 3 ( CNS effects) Aspiration Hazard Category 1

**GHS Label Elements:**

**Danger!**

**Statements of Hazard**

Combustible liquid  
 May be fatal if swallowed and enters airways  
 Causes skin irritation  
 May cause drowsiness or dizziness  
 Suspected of causing cancer  
 Suspected of damaging fertility or the unborn child

**Precautionary Statements Prevention**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, sparks, open flames, and hot surfaces. -  
 No smoking.



# Safety Data Sheet

**STP Products Manufacturing Company**

44 Old Ridgebury Road  
 Suite 300  
 Danbury, CT 06810  
 Tel. 1-203-205-2900

**Response**

IF SWALLOWED: Immediately call a POISON CENTER or doctor  
 Do NOT induce vomiting.  
 IF ON SKIN: Wash with plenty of water and soap.  
 If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor if you feel unwell.  
 IF exposed or concerned: Get medical advice.  
 In case of fire: Use water fog, foam, carbon dioxide or dry chemical to extinguish.

**Prevention – cont.**

Avoid breathing mist, vapors or spray.  
 Wash exposed skin thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves, and protective clothing.

**Storage**

Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
 Store locked up.

**Disposal**

Dispose of contents and container in accordance with local and national regulations.

**Hazards not otherwise specified:** None

**Percentage of unknown toxicity:** None

**3. Composition/Information on Ingredients**

Component	CAS No.	Amount
Hydrodesulfurized Kerosene	64742-81-0	85-95%
Solvent naphtha (petroleum), light aromatic	64742-95-6	5-10%
Solvent naphtha (petroleum), Heavy aromatic	64742-94-5	1-5%
1,2,4-Trimethylbenzene	95-63-6	<3%
Xylene	1330-20-7	<2%
Ethylbenzene	100-41-4	<1%
Naphthalene	91-20-3	<1%
Toluene	108-88-3	<1%
Cumene	98-82-8	<1%

**The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.**

**4. First Aid Measures**

**Inhalation:** If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. If breathing has stopped, administer artificial respiration. Get medical attention if symptoms appear and persist.

**Skin Contact:** Remove contaminated clothing and launder before reuse. Wash exposed skin with soap and water. If skin irritation or redness develops, get medical attention.

**Eye Contact:** Flush eyes with large amounts of water. If irritation or other symptoms persist, get medical attention.

**Ingestion:** DO NOT induce vomiting. If the victim is fully conscious, have them rinse their mouth with water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.



## Safety Data Sheet

### STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**Most Important Symptoms:** Skin irritant. Inhalation of mists or vapors may cause central nervous system effects such as dizziness, drowsiness, headache and nausea. Aspiration hazard – may enter the lungs during swallowing or vomiting and cause serious lung damage, which may be fatal. Ingestion may also cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects. Contains materials suspected of damaging fertility or the unborn child. Contains materials that may cause cancer based on animal data. This risk of cancer depends on the level and duration of exposure.

**Indication of Immediate Medical Attention/Special Treatment:** Immediate medical treatment is required for ingestions which may result in an aspiration hazard. Material may enter the lungs during swallowing or vomiting and cause serious lung damage, which may be fatal.

### 5. Firefighting Measures

**Suitable (and Unsuitable) Extinguishing Media:** Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

**Specific Hazards Arising from the Chemical:** Combustible liquid and vapor. Vapors may accumulate in confined areas and present a fire or explosion hazard. Vapors may be heavier than air and travel along surfaces to remote ignition sources and flash back. Closed containers may rupture if exposed to extreme heat. Burning may produce carbon monoxide, carbon dioxide and oxides of nitrogen.

**Special Fire Fighting Procedures:** Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

### 6: Accidental Release Measures

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Caution – slip hazard. Eliminate all ignition sources and ventilate the area. Wear appropriate protective equipment.

**Methods and Materials for Containment and Clean-Up:** Stop spill at the source if it is safe to do so. Absorb with an inert material. Collect into a suitable container for disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard.

**Environmental Precautions:** Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.

### 7. Handling and Storage

#### Precautions for Safe Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mists. Wash exposed skin thoroughly with soap and water after use. Keep containers closed when not in use. Do not permit smoking in use or storage areas. Keep out of the reach of children.

Empty containers retain product residue and may be hazardous. Do not reuse empty containers.

#### Conditions for Safe Storage, Including any Incompatibilities:

Store in a cool, dry, well-ventilated area. Keep container tightly closed. Store locked up. Store away from oxidizing agents and other incompatible materials. Keep away from open flames, sparks, and excessive heat.



# Safety Data Sheet

**STP Products Manufacturing Company**

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

## 8. Exposure Controls / Personal Protection

CHEMICAL	EXPOSURE LIMIT
Hydro sulfurized Kerosene (as total hydrocarbon vapor)	200 mg/m <sup>3</sup> TWA ACGIH TLV (Skin)
Solvent naphtha (petroleum), light aromatic	None Established
Solvent naphtha (petroleum), Heavy aromatic	None Established
1,2,4-Trimethylbenzene	25 ppm TWA ACGIH
Xylene	100 ppm TWA OSHA PEL 100 ppm TWA, 150 ppm STEL ACGIH TLV
Ethylbenzene	100 ppm TWA OSHA PEL 20 ppm TWA ACGIH TLV
Naphthalene	10 ppm TWA OSHA PEL 10 ppm TWA ACGIH TLV (Skin)
Toluene	20 ppm TWA ACGIH TLV 200 ppm TWA, 300 ppm Ceiling, 500 ppm 10 min peak per 8 hr. shift OSHA PEL
Cumene	50 ppm TWA OSHA PEL (Skin) 50 ppm TWA ACGIH TLV

**Ventilation:** General ventilation should be adequate for all normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

**Respiratory Protection:** None under normal use conditions. For operations where the exposure limits are exceeded, a NIOSH approved respirator with an organic vapor cartridge or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**Gloves:** Impervious gloves such as neoprene or nitrile are recommended if needed to avoid prolonged or repeated skin contact.

**Eye Protection:** Safety glasses or goggles are recommended if eye contact is possible.

**Other Protective Equipment/Clothing:** Appropriate protective clothing as needed to prevent prolonged or repeated skin contact.

## 9. Physical and Chemical Properties

**Appearance and Odor:** Clear, colorless to straw colored liquid with a hydrocarbon odor.

<b>Physical State:</b> Liquid	<b>Odor Threshold:</b> Not available
<b>pH:</b> Not applicable	<b>Vapor Pressure:</b> Not determined
<b>Initial Boiling Point/Range:</b> Not determined	<b>Vapor Density:</b> >1
<b>Melting/Freezing Point:</b> Not determined	<b>Percent Volatile:</b> 100%
<b>Solubility in Water:</b> Insoluble	<b>Evaporation Rate:</b> Not determined
<b>Viscosity:</b> Not determined	<b>VOC Content:</b> Not determined
<b>Specific Gravity:</b> 0.81	<b>Autoignition Temp:</b> Not determined



# Safety Data Sheet

**STP Products Manufacturing Company**

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

<b>Coefficient Of Water/Oil Distribution:</b> Not determined	<b>Flame extension:</b> Not applicable
<b>Flash Point:</b> 143°F (62°C) Setaflash	<b>Flammability (solid, gas):</b> Not applicable
<b>Flammability Limits:</b> LEL: Not Determined UEL: Not Determined	<b>Decomposition Temperature:</b> Not available

## 10. Stability and Reactivity

**Reactivity:** Not normally reactive

**Chemical Stability:** Stable under normal storage and handling conditions.

**Possibility of Hazardous Reactions:** None expected.

**Conditions to Avoid:** Keep away from excessive heat and open flames.

**Incompatible Materials:** Strong oxidizing agents and reducing agents

**Hazardous Decomposition Products:** Burning may produce carbon monoxide and carbon dioxide, aldehydes and unburned hydrocarbons.

## 11. Toxicological Information

### Potential Health Effects:

#### **Acute Hazards:**

**Inhalation:** Inhalation of mists or vapors may cause central nervous system effects such as dizziness, drowsiness, headache and nausea.

**Skin Contact:** Causes skin irritation. Prolonged or repeated contact may cause defatting and drying of the skin and dermatitis.

**Eye Contact:** Direct contact may cause eye irritation with redness, tearing and pain.

**Ingestion:** Aspiration hazard – may enter the lungs during swallowing or vomiting and cause serious lung damage, which may be fatal. Ingestion may also cause gastrointestinal effects such as nausea, vomiting and diarrhea and central nervous system effects with symptoms of drowsiness, headache, dizziness and unconsciousness.

**Chronic Effects:** Prolonged or repeated overexposure may cause adverse effects on the blood, and liver. Toluene is suspected of damaging fertility or the unborn child.

**Carcinogenicity Listing:** Naphthalene, Cumene and Ethylbenzene are classified by IARC as a possible human carcinogen (group 2B). Naphthalene and Cumene are classified by NTP as a reasonably anticipated human carcinogen. None of the other ingredients of this product are listed as carcinogens by IARC, NTP, or OSHA.

### Numerical Measures of Toxicity:

Product Calculated ATE:      LD50 Oral: >5000 mg/kg  
   LD50 Skin: >2000 mg/kg  
   LC50 Inhalation: >25 mg/L

Hydro-sulfurized Kerosene:      LD50 Oral Rat: >5000 mg/kg  
   LD50 Skin Rabbit: >2000 mg/kg  
   LC50 Inhalation Rat: >5.28 mg/L/4 hr.

Solvent naphtha (petroleum), light aromatic:



## Safety Data Sheet

### STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

	LD50 Oral Rat: 3500 mg/kg LD50 Skin Rabbit: >3160 mg/kg
Solvent naphtha (petroleum), Heavy:	LD50 Oral Rat: >5000 mg/kg LD50 Skin Rabbit: >2000 mg/kg LC50 Inhalation Rat >5.28 mg/L/ 4 hr.
1,2,4-Trimethylbenzene:	LD50 Oral Rat: 3280 mg/kg LD50 Skin Rabbit >3160 mg/kg LC50 Inhalation Rat: 18 mg/L/4 hr.
Xylene:	LD50 Oral Rat: 4300 mg/kg LD50 Skin Rabbit: >1700mg/kg LC50 Inhalation Rat: 20 mg/L/4 hr
Ethylbenzene:	LD50 Oral Rat: 3500 mg/kg
Naphthalene:	LD50 Oral Rat: 2200-2600 mg/kg LD50 Skin Rabbit >2000 mg/kg
Toluene:	LD50 Oral Rat: 5580 mg/kg LD50 Skin Rabbit: >5000 mg/kg LC50 Inhalation Rat: >20 mg/L/4 hr.
Cumene:	LD50 Oral Rat: 2910 mg/kg LD50 Skin Rabbit 10578 mg/kg LC50 Inhalation Rat 8000 ppm/4 hr

## 12. Ecological Information

### Ecotoxicity:

Hydro-sulfurized Kerosene:	EL50: Daphnia Magna: 1.4 mg/L/48 hr.
Solvent naphtha (petroleum), light aromatic:	LC50: Oncorhynchus mykiss 9.22 mg/L/96 hr. EC50: Daphnia Magna: 6.14 mg/L/48 hr.
Solvent naphtha (petroleum), Heavy:	LL50: Oncorhynchus mykiss 25 mg/L/96 hr. EL50: Daphnia Magna: 1.4 mg/L/48 hr.
1,2,4-Trimethylbenzene:	LC50: Oncorhynchus mykiss 9.22 mg/L/96 hr. EC50: Daphnia Magna: 6.14 mg/L/48 hr.
Xylene:	LC50 Rainbow Trout 13.5 mg/L/96 hr.
Ethylbenzene:	LC50 Pimephales promelas (fathead minnow) 14.4 mg/l /96 hr.
Naphthalene:	LC50 Oncorhynchus gorbuscha (pink salmon) 1.4 mg/L/96 LC50 Daphnia magna (Water flea) 2.16 mg /L/48 hr.
Toluene:	LC50 Oncorhynchus kisutch 5.5 mg /L/ 96 hr.



## Safety Data Sheet

### STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

Cumene: LC50: Fathead Minnow 6.32 mg/L/96 hr.  
LC50: Daphnia 3.44 mg/L/48 hr.

#### Persistence and Degradability:

Hydrosulfurized Kerosene: 58.6 % in 28 days  
Xylene: Readily biodegradable  
Ethylbenzene: After a period of inocula adaptation, ethylbenzene is biodegraded fairly rapidly by sewage or activated sludge inoculua.  
Naphthalene: Reached 2% of its theoretical BOD in 4 weeks  
Toluene: Readily biodegradable  
Cumene: Not readily biodegradable

#### Bio accumulative Potential:

Xylene: BCF 6 – 23.4  
Ethylbenzene: BCF of 15.  
Naphthalene: BCF 23 to 146, these BCF values suggest the potential for bio concentration in aquatic organisms is low to high.  
Toluene: BCF 90  
Cumene: Not likely to bio accumulate in aquatic organisms

#### Mobility in Soil:

Xylene: Low mobility in soil.  
Naphthalene: Is expected to have moderate to low mobility in soil.  
Cumene: Low mobility in soil.

**Other Adverse Effects:** No data available

### 13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations.

### 14. Transport Information

**DOT Hazardous Materials Description:** Not Regulated in non-bulk packagings (119 gallons and smaller).

**Canadian TDG Hazardous Materials Description:** Not regulated in small means of containment.

**IMDG Dangerous Goods Description:** Not Regulated for inner packages containing <5 L / 5 kg.

### 15. Regulatory Information

#### United States:

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has an RQ of 1000 lbs. based on the RQ for naphthalene of 100 lbs. present at 10% maximum. Oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.



# Safety Data Sheet

**STP Products Manufacturing Company**

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**SARA Hazard Category (311/312):** Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372):

1,2,4-Trimethylbenzene <3%  
Naphthalene <1%  
Ethyl Benzene <1%  
Toluene <1%  
Cumene <1%

## 16. Other Information

NFPA Rating (NFPA 704):	Health: 2	Fire: 2	Instability: 0
HMIS Rating:	Health: 2*	Fire: 2	Physical Hazard: 0
*Chronic Health Hazard			

REVISION DATE: 01/31/2018

REVISION SUMMARY: New SDS. Formula template

PREVIOUS REVISION DATE: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH